	Features	Benefits	
Features & Benefits	Translucent (i.e. semi-transparent) finish.	Highlights the natural features of the timber.	
	A moisture vapour permeable finish.	Allows the controlled passage of moisture, thus extending the lifespan of the coating and substrate.	
	Contains a mould inhibitor and fungicides.	Prevents disfiguration of the finish due to mould growth, surface fungi and blue stain.	
	Contains a resin to fix the active ingredients in the coating.	The finish is water repellent, with no risk of active ingredients being leached out.	
	Thixotropic and high viscosity formulation.	Reduces the risks of sagging and offers increased durability, and greater dimensional stability to windows and doors.	

GORI 88

Product Range 7802 Pine 7804 Teak 7805 Oak 7807 Dark Oak 7808 Walnut 7809 Redwood 7810 Palisander 7811 Ebony 8504 Swedish Red 8715 Light Blue 9900 Clear

	V V	
Product	GORI 88	
Content	Alkyd resin dissolved in white spirit	
Colour	Coloured for outdoor application	
Finish	Translucent. Semi-gloss sheen	
Application Rate	10-12 m ² on smooth planed hardwood	
Application	Approximately 60 μm per coat minimum w.f.t.	
Volume Solids	Approximately 40%	
Drying Time	5-7 hours (touch-dry), 12-18 hours (recoatable)	
Flash Point	58°C	
Density	0.9 ± 0.2 g/ml	
Cleaning	White spirit	
Packing	0.75 and 5 litres	
Storage	Above 5°C. Shelf life 24 months in unopened can	

System treatments - softwood and hardwood

Recommended Specification

Area of application	Primer	Intermediate	Top coat
Facades, fascias and fences	GORI 44 all round before installation	1 coat GORI 44	1 coat GORI 88
Windows and Doors	GORI 44 all round before installation	1 coat GORI 88	1 coat GORI 88

Natur Woodcare (M) S/B 21, Jln. PJS 11/7, Bandar Sunway, 46150 P.Jaya, Selangor. Tel: +603 5632 3272 Fax: +603 5632 3271 www.dyrup.com

GORI® is a registered trademark of Dyrup A/S Copyright® Dyrup A/S June 2009

