|                             | Features                                             |                                                                 | Benefits                                                                                              |  |
|-----------------------------|------------------------------------------------------|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|--|
| Features & Benefits         | Colourless and odourless when dry.                   |                                                                 | Does not affect the colour and final appearance of translucent woodstain finishes.                    |  |
|                             | Contains biocides, fungices and insecticides.        |                                                                 | Provides 'in-depth protection' against blue stain fungal decay and insects including termites.        |  |
|                             | Reduction of swelling.                               |                                                                 | Excellent dimensional stability.                                                                      |  |
|                             | The chemicals are 'fixed' into the timber substrate. |                                                                 | Chemicals will not leached out by water or weathering.                                                |  |
|                             | Can be brush or sprayed without corroding metal.     |                                                                 | Ideal for on-site treatment or factory application with no restriction on metal fasteners or fixings. |  |
|                             |                                                      |                                                                 |                                                                                                       |  |
| GORI 22                     | Product                                              | GORI 22                                                         |                                                                                                       |  |
| Product Range<br>9900 Clear | Content                                              | Cipermetrine, Propiconazole, IPBC and Tebuconazole              |                                                                                                       |  |
|                             | Colour                                               | Colourless                                                      |                                                                                                       |  |
|                             | Finish                                               | Non film forming                                                |                                                                                                       |  |
|                             | Application Rate                                     | 4-6 m² on medium hardwood                                       |                                                                                                       |  |
|                             | Application                                          | Until saturation                                                |                                                                                                       |  |
|                             | Volume Solids                                        | Approximately 5%                                                |                                                                                                       |  |
|                             | Drying Time                                          | 2 hours (touch-dry), 24 hours (recoatable for solvent products) |                                                                                                       |  |
|                             | Flash Point                                          | 67°C                                                            |                                                                                                       |  |
|                             | Density                                              | 0.8 ± 0.1 g/ml                                                  |                                                                                                       |  |
|                             | Cleaning                                             | White spirit                                                    |                                                                                                       |  |
|                             | Packing                                              | 0.75, 5, 15 and 200 litres                                      |                                                                                                       |  |
|                             | Storage                                              | Above 5°C. Shelf life 24 months in unopened can                 |                                                                                                       |  |
|                             |                                                      |                                                                 |                                                                                                       |  |
|                             | System treatment                                     | nts - softwood a                                                | and medium hardwood                                                                                   |  |
| Recommended Specification   | Area of application                                  | Area of application                                             |                                                                                                       |  |
|                             | All non-durable timber                               | Apply GORI 22 until saturation                                  |                                                                                                       |  |

Natur Woodcare (M) S/B 21, Jln. PJS 11/7, Bandar Sunway, 46150 P.Jaya, Selangor. Tel: +603 5632 3272 Fax: +603 5632 3271 www.dyrup.com

GORI® is a registered trademark of Dyrup A/S Copyright® Dyrup A/S June 2009

